

PANTUM

The New Era for Printing

P3300 Series
Monochrome Laser Printer

Reduce your printing cost at utmost

Let the new Pantum P3300 series bring your business value with auto-duplex high speed printing for high working efficiency, low paper jam rate for fluent operation, and eco-friendly separate drum unit and toner cartridge to reduce your cost at utmost. It is ideally suited for users no matter from small business group or from large shared workgroup who require affordable running cost.



Silent printing mode to lower the noise and create a comfortable office environment



High
Print Speed



Low paper jam rate
design for engine



Convenient
to Print



Separate
Drum and Toner

PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



P3300 Series Monochrome Laser Printer

Model	P3300DN	P3300DW
Printing		
Print technology	Mono laser	
Print speed	33ppm(A4)/35ppm(Letter)	
First print out time	Less than 8.5 seconds	
Max. monthly volume	25000 pages	
Recommended monthly volume	250 to 3,000 pages	
Processor speed	350 MHz	
Memory	256 MB	
Resolution(dpi)	1200x600 dpi (Max)	
Printer language	PCL5e,PCL6,PS,PDF	
Duplex mode	Auto	
Control panel	2Line LCD	
NFC print	No	Yes
Network print	Yes	
Wireless print	No	Yes
Paper handling		
Paper input tray	250 pages	
Multipurpose tray	1 pages	
Paper output tray	120 pages	
Media types	Plain,Thick,Transparency, Cardstock, Lable, Envelope	
Media sizes	A4, A5, JIS B5, ISO B5 , A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2	
Media weight	Input tray: 60-105g/m ² Multipurpose tray: 60-200g/m ²	
General		
Dimensions (wxdxh)	354 x334x 232mm(13.9x 13.1x9.1in)	
Weight (without toner cartridge)	6.8kg (15lb)	
Operating temperature range	10-32 °C (50-95 °F)	
Operating humidity range	20% - 80% RH	
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%,+10%), 50/60Hz(±2Hz), 4.5A	
Noise	Printing: ≤52dB(A) Standby: ≤30dB(A) Silent mode: ≤46dB(A)	
Power consumption	Print: Average 525W Standby: 50W Dormant: Less than 2W	
Operating system compatibility	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.11; Linux (ubuntu12.04/14.04);	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.11; Linux (ubuntu12.04/14.04); iOS 6.0 above(iOS 6.0 not included); Android 4.0 and above
Interface	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n
Supplies		
Cartridge style ⁽¹⁾	Separate drum and toner	
Starter cartridge capacity	TL-410 (1500 pages)	
Standard capacity toner/drum	TL-410 (1500 pages) , TL-410H (3000pages) / DL-410(12000pages)	
Starter drum unit lifetime <small>(Print with A4 paper page by page discontinuously)</small>	DL-410 (12000 pages)	
What's in the box		
Printer × 1/ 1,500 Page Toner Cartridge × 1/ 12,000 Page Drum unit × 1/ USB Interface Cable × 1/ Power Cord × 1/ CD-ROM × 1/ Quick Setup Guide × 1		

(1) Average yield per toner cartridge in accordance with ISO/IEC 19752 (Individual users will experience different results based on their environment and page coverage)

Copyright ©2016 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.